

**Listing of the Claims:**

1. (Previously Presented) An elongated structure for the transmission of fluid-based compositions at non-ambient temperatures comprising:

    a conduit for the transmission of a fluid-based composition;

    at least two flexible elongated temperature control conduits for the transmission of a temperature control fluid, each of said temperature control conduits having a pair of generally opposing walls, wherein a first wall is positioned radially outward relative to said transmission conduit, a second wall is positioned radially inward relative to said transmission conduit, a relatively rigid elongated reinforcement member positioned in one of the first and second walls and projecting inwardly into the temperature control conduit, and a tab projecting outward from the wall in which the reinforcement member is positioned, wherein said at least two flexible elongated temperature control are composed of a flexible polymeric material; and

    an elongated cover holding said elongated temperature control conduits in thermal communication with said transmission conduit, wherein the cover has an outwardly oriented surface and an opposed inwardly oriented surface disposed radially inward thereof, and at least two elongated pockets defined on the inwardly oriented surface of the elongated cover, each pockets containing the projecting tabs of the associated flexible elongated temperature control conduit, the pockets positioned on the inward surface such that the flexible elongated temperature control conduits are positioned in spaced relationship to one another, the outwardly oriented surface of the cover in radial spaced relationship to the first conduit and defining a

cavity spaced between the cover and the first conduit, wherein the flexible elongated conduits are positioned in said cavity, wherein said flexible elongated temperature control conduits are positioned between the transmission conduit and the elongated cover.

2. (Previously Presented) The structure of claim 1 wherein said elongated cover comprises a fluid-tight outer conduit enclosing said temperature control conduit and said conduit.

3. Cancelled

4. (Original) The structure of claim 2 wherein said outer conduit contains no integral structural reinforcement.

5. (Original) The structure of claim 2 wherein said outer conduit includes no superficial structural reinforcement.

6. (Previously Presented) The structure of claim 1 wherein said reinforcement member extends radially with respect to said conduit and wherein said tab is positioned on the first wall of the elongated conduit and projects outward from the first wall perpendicularly with respect to said reinforcement member.

7. (Previously Presented) The structure of claim 6 wherein said temperature control conduit has a pair of generally opposing walls, a first wall radially outward relative to said transmission conduit and a second wall radially inward relative to said conduit.

8. Cancelled

9. (Previously Presented) The structure of claim 6 wherein tab has a configuration that is generally planar .

10. (Original) The structure of claim 9 wherein said reinforcement member comprises a radially extending body and said reinforcement tab extends circumferentially of said body.

11. (Original) The structure of claim 1 further comprising a sensor within said cover for detecting the pressure of said temperature control fluid outside of said temperature control conduit.

12. (Previously Presented) The structure of claim 1 wherein a pair of polymeric temperature control conduits are held on generally opposing sides of said transmission conduit and wherein the temperature control conduits contact each other when in position relative to the transmission conduit.

13. (Original) The structure of claim 1 wherein said temperature control conduit is inflatable by the introduction of said temperature control fluid.

14. Cancelled

15. (Previously Presented) The structure of claim 1 wherein the first wall of said temperature control conduit is arcuate and radially outward relative to said transmission conduit and the -second wall is radially inward relative to said transmission conduit.

16. (Previously Presented) The structure of claim 1 wherein the first wall of the flexible elongated temperature control conduit is radially outward relative to said transmission conduit and the second wall is arcuate and is radially inward relative to said transmission conduit.

17. Cancelled

18. Cancelled

19. Cancelled

20. Cancelled

21. Cancelled

22. Cancelled

23. (Previously Presented) An assembly for providing temperature control for a fluid within a subject conduit conveying fluid in a fluid conveying direction, said assembly comprising:

an elongated flexible cover,

at least one temperature control conduit having a pair of opposed walls with one of said walls disposed proximate to the subject conduit and another of the pair disposed a spaced distance therefrom, a relatively rigid inner rib extending along substantially the length of said temperature control conduit, and a tab projecting outwardly from the conduit at a location proximate to the inner rib, said temperature control conduit disposed within said cover and configured to convey temperature control fluid in a temperature control fluid direction fluid, wherein the tab is connected to the cover; and

a releasable fastener to hold said cover around said subject conduit such that said temperature control conduit is in thermal communication with said subject conduit and the temperature control fluid direction and the subject fluid conveying direction are parallel to each other;

wherein said elongated cover has at least one elongated pocket for receiving said tab configured on said temperature control conduit for holding said temperature control conduit relative to said elongated cover.

24. Cancelled

25. (Previously Presented) The assembly of claim 23 wherein said elongated cover comprises a flexible homogenous material.

26. (Original) The assembly of claim 23 wherein said cover contains no integral structural reinforcement.

27. (Previously Presented) The assembly of claim 23 wherein said tab is an elongated planar member.

28. (Original) The assembly of claim 27 wherein said rib comprises a radially extending body and said reinforcement tab extends circumferentially of said body.

29. (Original) The assembly of claim 23 further comprising a sensor within said cover for detecting the pressure of said temperature control fluid outside of said temperature control conduit.

30. Cancelled

31. Cancelled

32. Cancelled

33. (Original) The assembly of claim 23 wherein said temperature control conduit has a pair of generally opposing walls, a first wall and an arcuate outwardly curving second wall.